All-in-one Broadband Wireless Outdoor Solutions (AP/ Wireless Client /Repeater/Wireless Bridge) Model No: GAP-24005g









Wireless LAN IEEE802.11b/g compliant

Solid housing provides protection against rigorous weather conditions IP68 compliant

Four operating modes support: AP ,Wireless Client ,Repeater and Wireless Bridge

Strong network security with 64/128/152-bit WEP encryption and WPA

Provides "RSSI" indication for AP, Repeater and Wireless Bridge

Power over Ethernet design IEEE802.3af compliant

Spectifications

Standards Compliance	IEEE802.11b/g; IEEE802.3af; IEEE802.3; IEEE802.3u	
SDRAM	8 M Byte	
Flash	2 M Byte	
Radio Frequency Type	DSSS or OFDM	
Frequency Band	America/FCC:2.412~2.462GHz(11 channels)	
	Europe CE/ETSI:2.41~2.472 GHz(13 channels)	
Transmission Power	IEEE802.11b/g:20dBm	
Transmission Rate	IEEE802.11b:1/2/5.5/11 Mbps	
	IEEE802.11b/g:6/9/12/18/24/36/48/54 Mbps	

	Super g: up to 108 Mbps	
Access Point Interfaces	Auto MDI/MMDI-X Ethernet 10/100Base-TX: RJ-45	
Sensitivity	-86dBm @ 11Mbps,PER< 8%;-64dBm @ 54Mbps,PER< 10%	
Connector Type	None	
Security Systems	64-bit/128-bit/152-bit/ WEP encryption and Wi-Fi Protected	
	Access(WPA)	
Wireless Setting	Operation Mode-AP/Wireless Client/Repeater/Bridge(WDS)PtP	
	and PtMP Mode	
Software/Firmware	Site Survey	
	DHCP Client	
	Wireless access control by MAC address (deny or accept)	
	WPA Support (WPA personal and enterprise)	
	Web-based configuration via popular browser (MS IE, Netscape)	
	Windows "Locator" program to help find IP in DHCP client mode	
	Firmware upgrade and configuration backup via Web	
	Reset to default by WebUI	
Operating Environment	Operating Temperature:-10~+70	
PoE	AC 100V~240V;DC 12Volt ±5%;2A(Max.)	
Network Management	Windows 95/98/NT4.0/2000/XP	
System OS Support		
Warranty	One year limited	

Standard Accessories

GAP-24005g	SK30016C	PH65052A
	AND THE PARTY OF T	
AP+12dBi ANT	12V DC Injector/RJ45	Bracket

