

AS5600-52X

10GbE Data Center Switch

Bare-Metal Hardware



Product Overview

The Edge-Core AS5600-52X hardware switch meets the high-performance, availability, and network-scaling requirements of enterprise and cloud data centers. The AS5600-52X provides full line-rate switching at Layer 2 or Layer 3 across 48 x 10 GbE ports and 4 x 40 GbE uplinks. The switch can be deployed either as a Top-of-Rack switch, or as part of a 10 GbE or 40 GbE distributed spine, forming a non-blocking folded CLOS data center fabric.

The AS5600-52X hardware is designed for data centers, with a high port density of 64 x 10 GbE in a 1 RU enclosure; redundant, hot-swappable, load-sharing AC or 48 VDC* PSUs; fan tray with n+1 redundant fans; and port-to-power or power-to-port airflow options.

Key Features and Benefits

- Cost-effective, bare-metal switch infrastructure for data center fabric.
- 48 x SFP+ switch ports, supporting 10 GbE (DAC, 10GBASE-SR/LR/ER/LRM) or 1 GbE (1000BASE-T/SX/LX).
- 4 x 40 QSFP switch ports, supporting 40 GbE (DAC, 40GBASE-SR4/LR4) or 4 x 10 GbE (DAC or fiber breakout cable).
- Port Grouping to group 4 x 10G ports into one 40G port at the physical layer for maximum bandwidth utilization, and for 300m optical reach over MMF.
- Full line-rate Layer 2 or Layer 3 forwarding of 1.28 Tbps.
- Supports hot/cold aisle with port-to-power and power-to-port airflow SKUs.
- All ports on front; PSUs, fan tray on rear.
- Hot-swappable, load-sharing, redundant AC PSUs. 48VDC* option.
- Swappable fan tray with 3:1 fans.
- Energy Efficiency: 196 W typical power consumption.
- Management: Ethernet and console RJ-45 ports; USB storage port.
- Hardware switch pre-loaded with Open Network Install Environment (ONIE) for automated loading of compatible independent SwitchOS software.
- Compatible with Cumulus®Linux® r1.5.0 and later SwitchOS software from Cumulus Networks™.

Features

Ports

Switch Ports:
 48 x SFP+ each supporting 10 GbE or 1 GbE
 4 x QSFP each supporting 40 GbE or 4 x 10 GbE
 Management Ports on Front Panel:
 1 x RJ-45 serial console
 1 x RJ-45 100/1000BASE-T management
 1 x USB Type A storage port

Key Components

Switch Silicon: Broadcom BCM56846 Trident+ 640 Gbps
 CPU: Freescale P2020 dual-core 1.0 GHz
 Memory: 2 GB DDR3 SDRAM ECC
 Flash: 8 MB NOR Flash, 2 GB NAND Flash

Performance

Wire Speed Forwarding: L2 and L3
 Switching Capacity: 1.28 Tbps
 Forwarding Rate: 960 Mpps
 MAC Addresses: 128K
 VLAN IDs: 4K
 Jumbo frames (9216 Bytes)
 L3 Routes IPv4 16K, IPv6 8K
 Packet Buffer Size: 9 MB shared buffer pool
 Latency (RFC2544): 860 ns to 1.2 us (L2/L3, cut thru, full line rate)

LEDs

10G SFP+ Port LEDs: Link Speed, Link Status, Activity
 40G QSFP Port LEDs: Link Status, Activity
 Ethernet Management Port LED: Link Status, Activity
 Console Port LED: Link Status
 System LEDs: PSU1, PSU2, Diagnostic, Fans, Locator

Supported Optics and Cables

SFP+ Ports:
 10GBASE-CR DAC: 0.5 m to 7 m; Passive and Active
 10GBASE-SRL/SR: up to 100/300 m over OM3 MMF
 10GBASE-LR: Up to 10 km over SMF
 10GBASE-ER: Up to 40 km over SMF
 10GBASE-LRM: Up to 220 m over OM1/2/3 MMF
 1000BASE-SX, 1000BASE-LX, 100/1000BASE-T
 QSFP Ports:
 40GBASE-CR4 DAC; 0.5 m to 7 m; Passive and Active
 40GBASE-CR4 DAC to 4 x SFP+ 10GBASE-CR DAC;
 0.5 to 7 m
 40GBASE-SR4: Up to 100 m over OM3 MMF, 150 m over OM4 MMF
 40GBASE-SR4 to 4 x 10GBASE-SR: 100 m over OM3, 150 m OM4
 40GBASE-LR4: Up to 10 km over SMF

Software

Switch is loaded with Open Network Install Environment (ONIE) software installer
 Compatible with the following switchOS software:
 Cumulus Linux r1.5.0 and later

* Future Release

Physical and Environmental

Dimensions (WxDxH): 438.4 x 473 x 43.4 mm (17.26 x 18.62 x 1.71 inches)
 Weight: 8.5 kg (18.74 lbs), with two installed power supply modules
 Fan Tray: hot-swappable tray with 3+1 redundant fans
 Operating Temperature: 0°C to 40°C (32°F to 104°F)
 Storage Temperature: -40°C to 70°C (-40°F to 158°F)
 Operating Humidity: 5% to 95% non-condensing

Power

PSUs: 2 redundant, load-sharing, hot-swappable AC or 48VDC*
 Input Voltage: 90 to 264 VAC at 50-60 Hz. -48 to -72 VDC.
 Input Current: Max 6A @100/120 VAC, 3 A @200/240 VAC, 10 A @-72 VDC
 PSU Efficiency: Up to 93% for AC PSUs
 Max Power: 244 W, line-rate, 48 x 10 GBASE-SR, 4 x 40 GBASE-SR4, AC
 Typical Power: 196 W, no traffic, 48 x 10G DAC, 4 x 40 GBASE-SR4, AC

Regulatory

EMI
 CE Mark (EN55022 Class A)
 FCC Part 15 Class A
 VCCI
 Safety
 CB, EN 60950
 UL/CUL
 Environmental:
 Temperature: IEC 68-2-14
 Drop: ISTA 2A
 RoHS-6 Compliant

Warranty

Please check www.edge-core.com for the warranty terms in your country. The warranty provides return-to-factory hardware replacement for a three year period in North America.

For More Information

To find out more about Edge-Core Networks products and solutions, visit www.edge-core.com

About Edge-Core Networks

Edge-Core Networks is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edge-Core Networks delivers the software and systems that transform the way the world connects. Edge-Core Networks serves customers and partners worldwide. Additional information can be found at www.edge-core.com.

Edge-Core Networks is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edge-Core data center switches are developed and manufactured by Accton.

To purchase Edge-Core solutions, please contact your Edge-Core Network representatives at +886 3 563 8888 (HQ) or +1 (877) 828-CORE (877-828-2673) or authorized resellers.

© Copyright 2014 Edge-Core Networks Corp. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edge-Core Networks. Edge-Core Networks shall not be liable for technical or editorial errors or omissions contained herein.

Ordering Information

| | |
|--------------------|---|
| 5600-52X-O-AC-F-US | AS5600-52X 48-Port 10G SFP+ with 4x40G QSFP uplinks, ONIE software installer, dual AC PSUs, port-to-power airflow, N. America |
| 5600-52X-O-AC-B-US | AS5600-52X 48-Port 10G SFP+ with 4x40G QSFP uplinks, ONIE software installer, dual AC PSUs, power-to-port airflow, N. America |
| 5600-52X-O-AC-F-EU | AS5600-52X 48-Port 10G SFP+ with 4x40G QSFP uplinks, ONIE software installer, dual AC PSUs, port-to-power airflow, Europe |
| 5600-52X-O-AC-B-EU | AS5600-52X 48-Port 10G SFP+ with 4x40G QSFP uplinks, ONIE software installer, dual AC PSUs, power-to-port airflow, Europe |
| 5600-52X-O-AC-F-UK | AS5600-52X 48-Port 10G SFP+ with 4x40G QSFP uplinks, ONIE software installer, dual AC PSUs, port-to-power airflow, UK |
| 5600-52X-O-AC-B-UK | AS5600-52X 48-Port 10G SFP+ with 4x40G QSFP uplinks, ONIE software installer, dual AC PSUs, power-to-port airflow, UK |
| 5600-52X-O-AC-F-JP | AS5600-52X 48-Port 10G SFP+ with 4x40G QSFP uplinks, ONIE software installer, dual AC PSUs, port-to-power airflow, Japan |
| 5600-52X-O-AC-B-JP | AS5600-52X 48-Port 10G SFP+ with 4x40G QSFP uplinks, ONIE software installer, dual AC PSUs, power-to-port airflow, Japan |
| PSU-AC-400-F | 400W AC Power Supply FRU, port-to-power airflow, no power cord |
| PSU-AC-400-B | 400W AC Power Supply FRU, power-to-port airflow, no power cord |
| FAN-1U-1x4-F | Fan Tray FRU, port-to-power airflow |
| FAN-1U-1x4-B | Fan Tray FRU, power-to-port airflow |
| CBL-PWR-US | AC Power Cable - US (125V/13A, 1830mm)-- only required with spare power supplies |
| CBL-PWR-EU | AC Power Cable - Europe (250V/10A, 1830mm)-- only required with spare power supplies |
| CBL-PWR-UK | AC Power Cable - UK (250V/10A, 1830mm)-- only required with spare power supplies |
| CBL-PWR-JP | AC Power Cable - Japan-- only required with spare power supplies |
| 5600-52X-SVC-RTF | AS5600-52X Annual Hardware Service, Return-to-Factory |