



The POS1AP is a TRUE-FLAT Industrial POS System that offers variety of choices to retail applications. The Housing of POS1AP is made of ABS Plastic. With A+ Grade LED Display and Resistive Touchscreen, the POS1AP offers Quality with affordable price.

Configuration

Bundled with Fan-less N2800 or D525 or I3-3217U Power Packed CPU, the POS1AP delivers stable performance.

TRUE-FLAT Design & Smaller Foot Print

The POS1AP comes with ABS Plastic enclosure which enough ventilation at the back to keep the system cool at all the times. The Stand of POS1AP offers 90 degree angle for easy viewing. The TRUE-FLAT Screen is dust and water resistant.

Cable Management

The VESA Mount Stand offers cable management to eliminates clutter and & still occupies minimal counter space. The Footprint of POS1AP comes with Power adapter fitted at the base for cable management.

Optional Features

The POS1AP offers various options and add-on peripherals to meet customer's requirement. One of the most important features of POS1AP is its pre-fixed LCD Customer Display. The Customer Display is 2*20 and supports various languages. The POS1AP also supports three tracks Magnetic Card Reader

Specifications:

Display	15.1" LED Back lit, 4:3 Ratio		
Touch panel	ABON Resistive Touchscreen , 5W		
Chipset	Intel NM70 Chipset	Intel NM10 Chipset	Intel NM10 Chipset
Master board	I3-3217U with Fan	D525 with Fan	Fan-less N2800
CPU	Intel I3-3217 Dual core 1.8Ghz	Intel® Atom Dual Core D525 1.8Ghz	Intel® Atom dual core N2800 (1.86GHz)
RAM	Standard 2G DDR3 1333 1* SO-DIMM DDRIII 800/1066MHz, Max. Up to 4GB		
Storage	2.5" 320Gb SATA HDD	2.5" 320G SATA HDD	2.5" 320G SATA HDD
Video card	Intel HD Graphics	Intel GMA 3150	Intel® GMA3600
Network card	RTL8111E	RTL8103EL	RTL8111E
Watch Dog Timer	NA	NA	Support hardware reset function (L256, 0~255 seconds)
Sound card	Realtek HD ALC662	Realtek ALC662	Realtek HD ALC662
Interfaces			
RS232 COM ports	4	4	4
RS485	Optional	Optional	Optional
HDMI	1	Optional	Optional
USB	4	4	4
PS2 Mouse	1	1	1
PS2 Keyboard	1	1	1
LPT / Parallel	Optional	1	1
LAN	1	1	1
VGA	1	1	1
Environmental conditions			
Operating Temp	-10°C - +60°C	+5°C - +40°C	-10°C - +60°C
Operating Humidity	0% RH - 95%	15% RH - 85%	0% RH - 95%
Storage Temp	-20°C - +70°C	-30°C - +60°C	-20°C - +70°C
Storage Humidity	10% RH - 90% RH	10% RH - 90% RH	10% RH - 90% RH
Packaging Dimensions			
G.W	9kg		
Packing size	42*41*26cm		

I / O Panel



© 2012 PoS Tektronics Limited. The information contained herein is subject to change without notice.
PoS Tektronics Limited shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Intel, Core, is trademarks or registered trademarks of Intel Corporation or its subsidiaries in the U.S. and other countries. Please visit relevant websites for more information

PoS Tektronics Limited

Rooms 1318-19, 13 / F, Hollywood Plaza,
610 Nathan Road, Mongkok, Kowloon, Hong Kong

postektronics.com