

Delock External Enclosure 2 x CFast > USB 3.1 Gen 2 with RAID

Description

The aluminium enclosure by Delock enables the installation of two CFast memories, which can be connected via USB Type-C™ to the PC or laptop. When using more than one memory card, there is the possibility to use different RAID level.



Note

The package contains the cable USB-C™ male to USB Type-A male. This can also be used only in this direction. Therefore the USB-C™ male must be connected to the computer and the USB Type-A male to the enclosure. Optionally there is a cable from Delock USB Type-A male to USB Type-A male (83981), so that this enclosure can also be connected to a computer with USB Type-A interface. In addition, there is the possibility to connect a power supply if the power from the USB port is not enough.

Specification

- Connector:
 - external:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
 - 1 x 5 V DC jack
 - internal:
 - 2 x CFast 2.0 slot
- Chipset: Asmedia ASM1352R
- Supports CFast type I / II memory cards
- Downwards compatible to CFast 1.0
- Supports RAID 0, 1, SPAN, Port Multiplier
- RAID mode set by DIP switch on board
- Data transfer rate up to 10 Gbps
- Enclosure with full-PCB
- Colour: silver
- Dimensions (LxWxH): ca. 136 x 80 x 16 mm
- Hot Plug, Plug & Play

Specification of the power jack

- 5 V, ground outside, plus inside
- Dimensions:
 - inside: ø ca. 1.35 mm
 - outside: ø ca. 3.5 mm
 - length: ca. 8.5 mm
- Optional power supply: [Navilock 41337](#)

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6
- PC or laptop with a free USB Type-C™ or Thunderbolt™ 3 port

Package content

- External enclosure
- Cable USB-C™ male to USB Type-A male, length ca. 50 cm

Item No. 42582

EAN: 4043619425822

Country of origin: Taiwan, Republic of China

Package: Retail Box



- Cover, screwdriver, screws
- User manual

Images



General	
function:	Hot Plug Plug & Play
Internal construction:	full PCB
Supported operating system:	Linux Kernel 3.19 Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
Supported memory card:	CFast 1.0 and 2.0 CFast type I / II
Interface	
External:	1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Typ-A Buchse 1 x 5 V DC jack 3.5 mm x 1.35 mm
Internal:	2 x CFast 2.0 slot
Technical characteristics	
Chipset:	Asmedia ASM1352R
Data transfer rate:	USB 3.1 Gen 2 up to 10 Gb/s
RAID function:	SPAN 0 1 Port Multiplier
Physical characteristics	
Housing material:	Aluminium
Length:	136 mm
Width:	80 mm
Height:	16 mm
Colour:	silver