POS Printer

SOL 801

The SOL 801 is a High Speed thermal PoS printer designed for PoS & Kitchen Printing application. It has a high printing speed of 250 mm/sec. The top cover of SOL 801 is Piano Finish that goes along well with Stylish PoS Systems. Its rich interface selection includes USB, RS232, Parallel, Ethernet, Bluetooth & Wi-Fi version. The Printer has some vital features such as LED Panel to indicate that the printer is printing, Speakers that provides Voice messaging and changeable Interface Ports that helps in software compatibility

Features:

- Ultra High Printing Speed – 250mm/sec
- Piano Finish Top Cover
- Support LOGO Graphical download and print
- Support 1D, 2D barcode printing
- Support Multi-language printing
- Optional Voice messaging Feature
- Built-in Speaker
- Interface Options:
    - ✓ USB(Removable Port)
    - ✓ RS232 (Removable Port)
    - ✓ Parallel (Fixed)
    - ✓ LAN (Fixed)
    - ✓ USB+LAN+RS232 (Fixed Port)
- Built-in WEB server, configure printer by IE browser
- Support Windows, Linux, Android and IOS system printing

Specification:

Printing Method	Thermal Line
Resolution	8dots/mm, 576dots/line
Effective Printing Width	72mm
Printing Speed	250mm/s
Character Set	ASCII, GB18030(Chinese),BIG5,Codepage
Self-defined Character	YES
Print Font	Font A: 12 x24
Barcode	1D: UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128 2D: PDF417, QR CODE, DATAMATRIX
Graphic	Support bitmap downloading
Driver	Windows XP/win7/Win Vista/Win8/Win10
Paper End Sensor	YES
Overheating Protection	YES
Interface	RS232/Parallel/USB/RS232+USB+Ethernet / USB+Bluetooth/USB+Ethernet+Wifi
Cash drawer control	DC24V,1A, 6PIN RJ-11Socket
Power Supply (Adapter)	AC100 ~240V ± 10%(include) DC 24V, 2A
TPH	150KM
Auto Cutter	1,000,000 cuts
Paper Type	Thermal paper
Paper Width	79.5± 0.5mm
Paper Thickness	0.06 to 0.08mm
Paper Roll Diameter	Max. 80mm
Auto Cutter	Partial Cut
Operating Temp/Humidity	0-50°C/10%-80%
Storage Temp/Humidity	-20-60°C / 10%-90%
Weight	1.35kg（Net weight）/2.2kg（Including packing）
Dimension (LxWxH)	197*150*133mm