



Delock CFast-Card SATA 6 Gb/s 128 GB Typ MLC -40°C ~ +85°C

Description

This Delock CFast Flash Card supports the new CFast 2.0 standard and allows even higher data transfer rates than memory cards of the previous CFast generation. It is therefore ideally suited not only for professional usage in photography, but also for all other applications that require fast read and write speeds. CFast 2.0 memory cards use the SATA 6 Gb/s protocol and convince with lower power consumption. This CFast Card has an extended temperature range of -40 $^{\circ}$ C $^{\sim}$ + 85 $^{\circ}$ C and supports the functions NCQ, iSMART, TRIM and iDATA Guard.

NCQ: Native Command Queuing is a technique, which was developed in order to improve the performance of HDDs under certain circumstances.

ISMART: iSMART is a powerful, easy-to-use solidstate drive SSD and hard disk drive HDD monitoring tool.

TRIM: TRIM is a command for marking unused or unvalid data blocks on storage media for later rewriting.

iDATA Guard: iDATA Guard is a comprehensive data protection mechanisum, which reacts before and after a sudden power break down.



Specification

- · Capacity: 128 GB
- Interface: SATA 6 Gb/s
- · Chip: Toshiba
- Flash Typ: MLC
- Max. Channel: 2
- Maximum speed: 200 MB/s read, 110 MB/s write
- Maximum write cycles: 3000
- Maximum power consumption: 1.1 W
- $\bullet \ Thermal \ sensor: \ ST-Optional \ / \ WT-Default$
- H/W Write protect: Optional
- S.M.A.R.T.: Yes
- Dimensions (LxWxH): 36.4 x 42.8 x 3.6 mm
- Vibration: 20 G 7 ~ 2000 Hz
- Shock: 1500 G 0.5 ms
- MTBF: >3 million hours
- Storage temperature: -55°C ~ +95°C
- Operation temperature: Industrial Grade -40°C ~ +85°C

System requirements

A free CFast slot

Package content

CFast memory card

Item No. 54703

EAN: 4043619547036

Country of origin: Taiwan, Republic of

China

Package: Retail Box

