

| Model | On-Lap 1102H Monitor |
|---------------------------------|--|
| Panel | 11.6" (16:9 Wide) FFS (Fringe Field Switching) panel |
| Resolution / Surface | 1920 x1080 (16.7M colors) / Anti-Glare |
| Active Area | 256.32mm*144.18mm (WxH) |
| Pixel Pitch | 0.1335mm (H) *0.1335mm (V) |
| Viewing Angle(U/D/L/R) | 178°(H)/178°(V)(CR>10) |
| Contrast Ratio | 1000:1 (Typical) |
| Brightness | 350(cd/m2) |
| Response Time | 12.5(ms) (Typical) |
| Connectivity | HDMI*2(Micro HDMI port*1,Rear dock port*1),VGA*1 3.5mm mini jack 5V DC*1 (Micro USB) |
| Battery Capacity | 7,800mAH |
| Battery type | Li-Polymer |
| Usage time | 4.5 Hr (Brightness 70, Audio 50) |
| Charge time | 4 Hr |
| Supported Resolutions | 1920*1080(60Hz);1600*900(60Hz);1440*900(60Hz); 1366*768(60Hz) 1280*1024(60Hz);1280*960(60Hz);1280*800(60Hz); 1280*768(60Hz); 1280*720(60Hz); 1024*768(60Hz) |
| HDMI Video Display Capabilities | 1920x1080P(50Hz/59.94Hz/60Hz);1280x720P(50Hz/59.94Hz/60Hz); 720x480P(59.94Hz/60Hz); 640x480P(59.94Hz/60Hz) |
| Video Input | HDMI*2(Micro HDMI port*1,Rear dock port*1),VGA*1 |
| HDCP Support | Yes |
| Plug & Play | VESA DDC2B/C1 |

| | |
|------------------------|--|
| Audio Output | 3.5mm mini jack(Support both digital mini Toslink and Analog 3.5mm AUX) |
| Speakers | 2x 1.0W(Max.) (Rated Impedance 5.1Ω at 2KHz) |
| Power On(Max.) | ≤8.5W |
| Standby Mode | <0.5W |
| Power Off Mode | <0.5W |
| Rating Power | 5V---1.7A |
| Environment | Operating :0~50°C;Humidity:20~90%RH Storage:-20~60°C;Humidity:10~90%RH |
| Cabinet Colors | Front: Hazy Teal Rear: Gunmetal grey Cover stand: Black |
| Dimension(W/H/T) | 294mm*194mm*11mm(Monitor) 299mm*209mm*21mm(Monitor and cover) |
| Net Weight | 590g(Monitor) 840g(Monitor and cover) |
| Accessories in package | Cover Stand*1; 1/4" screw mount kit HDMI-A to micro-HDMI cable (1.2m)*1 USB-A to micro-USB cable (1.2m)*1 Mini-HDMI - Micro HDMI Video Cable (0.6m)*1 5V-2A adapter*1 |
| Optional Accessories | USB-A to Micro-USB power and touch signal cable (2.1m) On-Lap Proprietary VGA Cable (1.2m/2.1m) HDMI-A to Micro-HDMI Video Cable (2.1m) mini-HDMI to Micro-HDMI Video Cable (2.1m) On-Lap Proprietary HDMI-A and USB-A to Dock Port Cable(1.2m) Micro-HDMI to Micro-HDMI Video Cable (1.2m) Rear dock (HDMI-A, USB-A, USB-C ports) 1102 Multi-Mount Kit |
| Warranty | 1 Year Limited |
| Certification | BSMI, CE, C-Tick, FCC, KC, VCCI, RoHS |