

Model	On-Lap 1102I Monitor
Panel	11.6" (16:9 Wide) FFS (Fringe Field Switching) panel
Resolution / Surface	1920 x1080 (16.7M colors) / Anti-Glare
Active Area	256.32mm*144.18mm (WxH)
Pixel Pitch	0.1335mm (H) *0.1335mm (V)
Viewing Angle(U/D/L/R)	178°(H)/178°(V)(CR>10)
Contrast Ratio	1000:1 (Typical)
Brightness	250(cd/m2)
Response Time (GTG)	12.5(ms) (Typical)
Connectivity	HDMI*2(Micro HDMI port*1,Rear dock port*1),VGA*1 3.5mm mini jack 5V DC*1 (Micro USB)
Type of touch screen	Projective capacitive
Touch Points	10 detections
Operating System	Windows 10/ 8.1/ 7
Diameter of Touch Point	≥6.0mm
Screen Surface Hardness	≥ 7H
Stylus	Support capacitive type stylus(Diameter of conductive rubber≥ 6.0mm)
Supported Resolutions	1920*1080(60Hz);1600*900(60Hz);1440*900(60Hz); 1366*768(60Hz) 1280*1024(60Hz);1280*960(60Hz);1280*800(60Hz); 1280*768(60Hz); 1280*720(60Hz); 1024*768(60Hz)

HDMI Video Display Capabilities	1920x1080P(50Hz/59.94Hz/60Hz);1280x720P(50Hz/59.94Hz/60Hz); 720x480P(59.94Hz/60Hz); 640x480P(59.94Hz/60Hz)
Video Input	HDMI*2(Micro HDMI port*1,Rear dock port*1),VGA*1
HDCP Support	Yes
Plug & Play	VESA DDC2B/C1
Audio Output	Headphone Out
Speakers	2x 1.0W(Max.) (Rated Impedance 5.1Ω at 2KHz)
Power On(Max.)	≤8.5W
Standby Mode	<0.5W
Power Off Mode	<0.5W
Rating Power	5V---1.7A
Environment	Operating :0~50°C;Humidity:20~90%RH Storage:-20~60°C;Humidity:10~90%RH
Cabinet Colors	Front: Black Rear: Gunmetal grey Cover Stand: Black
Dimension(W/H/T)	294mm*194mm*11mm(Monitor) 299mm*209mm*21mm(Monitor and cover)
Net Weight	590g(Monitor) 840g(Monitor and cover)
VESA wall mount	VESA 75 (Optional Multi-mount Kit for 1102)
Accessories in package	Cover Stand*1; 1/4" screw mount kit HDMI-A to micro-HDMI cable (1.2m)*1 USB-A to micro-USB cable (1.2m)*1 Mini-HDMI - Micro HDMI Video Cable (0.6m)*1 5V-2A adapter*1
Optional Accessories	USB-A to Micro-USB power and touch signal cable (2.1m) On-Lap Proprietary VGA Cable (1.2m/2.1m) HDMI-A to Micro-HDMI Video Cable (2.1m) mini-HDMI to Micro-HDMI Video Cable (2.1m) On-Lap Proprietary HDMI-A and USB-A to Dock Port Cable(1.2m)

	Micro-HDMI to Micro-HDMI Video Cable (1.2m) Rear dock (HDMI-A, USB-A, USB-C ports) 1102 Multi-Mount Kit
Warranty	1 Year Limited
Certification	BSMI, CE, C-Tick, FCC, KC, VCCI, RoHS