

RCX-1000 Series

8th Generation Intel® Xeon®/Core™ i7/i5/i3 (Coffee Lake) Workstation-grade Fanless Robust Computing System

- 6 Cores 8th Generation Intel® Xeon®/Core™ i7/i5/i3 (Coffee Lake-S) with workstation-grade Intel® C246 Chipset
- 4 DDR4 2666MHz Memory, up to 128GB (ECC/Non-ECC)
- 6 ports external USB 3.1 Gen 2 support up to 10Gbps data transfer
- Rugged & Fanless design, -40°C to 75°C Operating Temperature
- Onboard DVI-I and DisplayPort display interface, up to 3 independent HD display
- 2 Independent GigE LAN, iAMT 12.0 supported
- 2 External SIM Socket for WiFi/4G/3G/LTE/GPRS/UMTS
- 4 Front-access 2.5" SSD Tray, RAID 0, 1, 5, 10 supported
- 4 PCI/PCIe Slot, max 300W Power Budget for independent graphics operation
- 32 Isolated DIO, 4 COM RS-232/422/485
- 2 M.2 Socket : 1 M.2 Key M, 1 M.2 Key E
- 6V to 36V DC Power Input with 80V Surge Protection
- Configurable Ignition Power Control



Robotic Control



Factory Automation



Intelligent Surveillance



Deep Learning



Specifications

System

Processor	6 Cores Intel® Xeon®/Core™ i7/i5/i3 Processor (Coffee Lake-S)
Chipset	Intel® C246
BIOS	AMI
SIO	IT8786E
Memory	4 DDR4 2666MHz SO-DIMM, up to 128GB (ECC/Non-ECC)
OS	Windows 10, Linux

I/O Interface

Serial	4 COM RS-232/422/485 (ESD 8KV)
USB	- 6 USB 3.1 Gen 2 (External) - 1 USB 2.0 (Internal)
Isolated DIO	32 Isolated DIO : 16 DI, 16 DO
LED	Power, HDD, Wireless
SIM Card	2 External SIM Card Socket

Expansion

Mini PCIe	2 Full-size for PCIe/USB/External SIM Card/mSATA
M.2	1 M.2 Key E Socket
PCIe	Up to 4 PCIe Slot, by request
PCI	Up to 4 PCI Slot, by request

Graphics

Graphics Processor	Intel® UHD Graphics P630/630
Interface	- 1 DVI-I : Up to 1920 x 1200 @60Hz - 2 DisplayPort : Up to 4096 x 2304 @60Hz

Storage

SATA	4 SATA III (6Gbps) support S/W RAID 0, 1, 5, 10
mSATA	2 SATA III (Mini PCIe Type, 6Gbps)
Storage Device	- 4 Front-access 2.5" SSD/HDD Tray - 1 M.2 Key M Socket

Audio

Audio Codec	Realtek ALC892, 5.1 Channel HD Audio
Audio Interface	1 Mic-in, 1 Line-out

Ethernet

LAN 1	Intel® I219LM GigE LAN supports iAMT 12.0
LAN 2	Intel® I210 GigE LAN

Power

Power Input	6V to 36V, DC-in
Power Interface	3-pin Terminal Block : V+, V-, Frame Ground
Ignition Control	16 Mode (Internal)
Remote Switch	3-pin Terminal Block
Surge Protection	Up to 80V/1ms Transient Power

Others

TPM	Optional Infineon SLB9665 supports TPM 2.0, LPC Interface
Watchdog Timer	Reset : 1 to 255 sec./min. per step
Smart Mgmt.	Wake on LAN, PXE supported
HW Monitor	Monitoring temperature, voltages. Auto throttling control when CPU overheats.

Mechanical

Dimensions	RCX-1400FR/RCX-1400F 330.0mm x 210.0mm x 172.0mm (12.99" x 8.27" x 6.77")
	RCX-1400R/RCX-1400 250.4mm x 210.0mm x 172.0mm (9.86" x 8.27" x 6.77")
Weight	RCX-1200 250.4mm x 210.0mm x 131.4mm (9.86" x 8.27" x 5.17")
	RCX-1400FR : 5.3 kg (11.7 lb) RCX-1400F : 4.9 kg (10.8 lb) RCX-1400R : 5.0 (11.0 lb) RCX-1400 : 4.6 kg (10.1 lb) RCX-1200 : 4.3 kg (9.5 lb)
Mounting	Wallmount by mounting bracket

Environment

Operating Temp.	35W TDP CPU : -40°C to 75°C (-40°F to 158°F)
	65W TDP CPU : -40°C to 55°C (-4°F to 131°F)
	80W TDP CPU : -40°C to 45°C (-4°F to 113°F)
Storage Temp.	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% Humidity, non-condensing
Relative Humidity	95% @ 75°C
Shock	- IEC 60068-2-27
	- SSD : 50G @ wallmount, Half-sine, 11ms
Vibration	- IEC 60068-2-64
	- SSD : 5Grms, 5Hz to 500Hz, 3 Axis
EMC	CE, FCC, EN50155, EN50121-3-2

CPU List

Series	CPU	Cache (MB)	Turbo Freq. (GHz)	TDP (W)	ECC Memory
Intel® Xeon®	E-2176G	12	4.6	80	Yes
	E-2124G	8	4.5	71	
Intel® Core™	i7-8700	12	4.6	65	NA
	i7-8700T	12	4.0	35	
	i5-8500	9	4.1	65	NA
	i5-8500T	9	3.5	35	
	i3-8100	6	3.6	65	Yes
	i3-8100T	6	3.1	35	

* The rights of all brand names, product names and trademarks belong to their respective owners.
Copyright © 2018 Vecow Co., Ltd. All rights reserved.

Order Information

Model Name	GigE LAN	PCIe x16	PCIe x8	PCIe x4	PCIe x1	PCI	SSD Tray	COM	USB 3.1	SIM	Isolated DIO
RCX-1430FR	2	1	-	1	1	-	4	4	6	2	Y
RCX-1430F	2	1	-	1	1	-	-	4	6	2	Y
RCX-1421FR	2	1	-	1	-	1	4	4	6	2	Y
RCX-1421F	2	1	-	1	-	1	-	4	6	2	Y
RCX-1412FR	2	1	-	-	-	2	4	4	6	2	Y
RCX-1412F	2	1	-	-	-	2	-	4	6	2	Y
RCX-1440R	2	-	1	3	-	-	4	4	6	2	Y
RCX-1440	2	-	1	3	-	-	-	4	6	2	Y
RCX-1422R	2	1	-	1	-	2	4	4	6	2	Y
RCX-1422	2	1	-	1	-	2	-	4	6	2	Y
RCX-1404R	2	-	-	-	-	4	4	4	6	2	Y
RCX-1404	2	-	-	-	-	4	-	4	6	2	Y
RCX-1220A	2	-	2	-	-	-	-	4	6	2	Y
RCX-1220	2	1	-	1	-	-	-	4	6	2	Y
RCX-1211	2	1	-	-	-	1	-	4	6	2	Y


Accessories

DDR4 32G	Certified DDR4 32GB 2666MHz RAM
DDR4 16G	Certified DDR4 16GB 2666/2400/2133 MHz RAM
DDR4 8G	Certified DDR4 8GB 2666/2400/2133 MHz RAM
DDR4 4G	Certified DDR4 4GB 2666/2400/2133 MHz RAM
PWA-160WB-WT	160W, 24V, 85V AC to 264V AC Power Adaptor with 3-pin Terminal Block (7.62mm pitch), Wide Temperature -30°C to +70°C
PWA-280WB-WT	280W, 24V, 85V AC to 264V AC Power Adaptor with 3-pin Terminal Block (7.62mm pitch), Wide Temperature -30°C to +70°C
PWS-480W-WT	480W, 24V, 90V AC to 305V AC Power Supply, Wide-Temp, IP65
PWS-600W	600W, 24V, 90V AC to 305V AC Power Supply
PWS-600W-WT	600W, 28.8V, 90 to 305V AC Power Supply, Wide Temperature -40°C to +70°C
FAN Module	Fan Module for RCX-1000 Series
FAN Sink	Fan Sink for RCX-1000 Series
PCIE HOLD-DOWN Kit	Hold Down Module for PCIe Card
TMK2-20P-100	Terminal Block 20-pin to Terminal Block 20-pin Cable, 100cm
TMK2-20P-500	Terminal Block 20-pin to Terminal Block 20-pin Cable, 500cm
TMB-TMBK-20P	Terminal Board with One 20-pin Terminal Block Connector and DIN-Rail Mounting
4G Module	Mini PCIe 4G/GPS Module with Antenna
WiFi & Bluetooth	WiFi & Bluetooth Module with Antenna



Dimensions & Drawing

Unit : mm (inch)


RCX-1400RF/1400R






RCX-1400F/1400



RCX-1400RF/1400F



RCX-1400R/1400



RCX-1200

