



SC-2168-WP WiFi IP phone with 3 SIP LINE, Wifi 2.4GHz (Wifi 5.8GHz option)



SC-2168-WP is a highly innovative based wireless SIP VoIP phone, It can perfectly satisfy with all kinds of the businessman communication. It integrates with 2.4" 132x64-pixel graphical LCD with backlight, a large resolution display screen, elegant and intuitive user interface, which indicate you can enjoy perfect user experience. SC-2168-WP offers high audio quality HD handset, HD speaker and HD codec (G.722), with a rich set of business communication features that can definitely improve working efficiency and sense. It is highly suitable for SMEs, Home Office and ISP applications.

SC-2168-WP Wi-Fi IP phone, help user connect the network simply and enjoy the network easily.

Key Features

- ♦ Wireless working **frequency 2.4GHz/5.8GHz.**
- ♦ 2.4" 132*64-pixel Graphical LCD with backlight.

- ◆ HD Voice: HD Codec, HD Speaker, HD Handset.
- ◆ Multi-language: Chinese, English, French, Russian, etc.
- ◆ One standard (42.5°) level bracket and wall-mountable.
- ◆ 3 SIP accounts and support three-way conference, SMS.
- ◆ 2xLAN, PoE (option), 1xRJ9Headset.
- ◆ XML/LDA, Contact Search.
- ◆ Auto-provision, HTTP/TFTP/FTP, Tr069.
- ◆ Support 15 paperless programmable keys.

Phone Features

- ◆ 3 SIP accounts, Hotline
- ◆ Call hold, Call waiting, Call forward, Call return
- ◆ Call transfer (blind/busy/ask)
- ◆ Caller ID display, Redial, Mute, DND
- ◆ Auto-answer, 3-way conferencing
- ◆ Speed dial, SMS, Voicemail
- ◆ Message Waiting Indication LED
- ◆ Tone scheme, Volume control
- ◆ Direct IP call without SIP proxy
- ◆ Ring tone selection/import/delete
- ◆ Phonebook (local up to 1000 entries)
- ◆ Black list, Hand-free indicator.
- ◆ Call history: dialed/received/missed (100 -entries); One-key back (C)
- ◆ Multi-Language (2aB/abc/ABC/123)
- ◆ Soft keys programmable, Supports PC control
- ◆ Support switching SIP server & Second server

Advanced Features

- ◆ XML Phone Book search and input & output
- ◆ Enterprise phone book(800 entries)
- ◆ LDAP phone book
- ◆ Aution URL & Active URI
- ◆ Functions customizable keys
- ◆ XML Browser

IP PBX System Integration

- ◆ Busy lamp field (BLF), BLF list
- ◆ Bridged line appearance (BLA)
- ◆ DND & Forward synchronization
- ◆ Intercom, Paging, Music on hold
- ◆ Call pickup, Dial Plan, Call recording

Codes and Voice

- ◆ Wideband Codec: G.722

Features

- ◆ Narrowband codec: G.711μ/A, G.723.1
- ◆ G.726, G.729AB,iLBC
- ◆ VAD, CNG, AEC, AGC, Full-duplex,

Security

- ◆ 802.1x, VLAN QoS (802.1pq), SRTP
- ◆ Transport Layer Security (TLS)
- ◆ Digest authentication using MD5/MD5-sess
- ◆ Secure configuration file via AES encryption
- ◆ Encryption for configuration file
- ◆ Phone lock for personal privacy protection
- ◆ Admin/User 2-level configuration mode , LLDP, CDP
- ◆ L2TP VPN tunneling protocol - added

Network Features

- ◆ SIP v1 (RFC2543), v2 (RFC3261)
- ◆ SIP connection: Proxy mode & Peering Points mode; IPV6 DNS SRV (RFC3263);
- ◆ SRTP voice encryption(RFC3711)
- ◆ Redundant server support
- ◆ NAT Traversal: STUN mode
- ◆ DTMF: In-Band, RFC2833, SIP Info, Auto
- ◆ HTTP/HTTPS Web Management
- ◆ IP Assignment: Static/DHCP/PPPoE
- ◆ Bridge/Router mode for PC port
- ◆ TFTP/DHCP/PPPoE client
- ◆ Telnet/HTTP/HTTPS server, DNS client, NAT/DHCP server
- ◆ Layer 3 ToS, DSCP

Management

- ◆ Auto-provision via FTP/TFTP/HTTP/HTTPS
- ◆ SNMP V1/2 , TR069
- ◆ Configuration: browser/phone/auto-provision
- ◆ Trace package and system log export

Physical Features

- ◆ 2.4"132x64 graphic LCD; 34 keys including 2 programmable keys; 1xRJ9 headset port; 2xRJ45 10/100M Ethernet ports;
- ◆ WIFI 5.8GHz
- ◆ Line keys with LED indicator: 3
- ◆ LED for call and message waiting indication;
- ◆ Dual-color (red or green) illuminated LEDs for line status information;
- ◆ 42.5° bracket and wall-mountable
- ◆ Power adapter: AC 100~240V input and
- ◆ DC 5V/1A output;
- ◆ Power over Ethernet ,IEEE 802.3af,class 0

- ◆ Power consumption: 1.4-2.6W
- ◆ Net weight:
- ◆ Dimension:
- ◆ Operating humidity: 10~95%
- ◆ Storage temperature: up to 60°C

Package Features

- ◆ Qty/CTN: 10 PCS
- ◆ N.W/CTN: 7.58kg
- ◆ G.W/CTN: 8.8kg
- ◆ Measurement: 0.068CBM($\pm 0.5\%$)
- ◆ Carton Meas: 455x390x222mm

SunComm TECHNOLOGY CO., LTD.

7F, No. 53, Jian-Kang Road, Chung Ho Dist, New Taipei City, Taiwan 23586

www.suncomm.com.tw www.3GfixedWirelessTerminal.com

Tel: +886-32341496 Fax: +886-2-32341393

China: www.suncomm.cn

Tel: +86-136 8884 2805 +86-138 2927 8505