

**ELECTRONIC TEST:**

1. 100% TEST, (Open, Short, Miss Wire).
2. Contact Resistance: 5Ω/max.
3. Insulation Resistance: 10MΩ/min.
4. Hi-Pot: 300v dc/0.01s.

CONN	WIER LIST		
P1	1	2	3
P2	1	2	3
COLOU	grey	grey	grey

PART LIST: All "ROHS" Compliant, All Materials are Equivalent.

ITEM	STANDARD SPECIFICATION		
5	BLACK HEAT SHRINK TUBE 2PCS	2	PCS
4	TERMINAL: SZE-002T-P0.3 JST.	3	PCS
3	HOUSING: SZE-002H-P0.3 JST	1	PCS
2	WJ15EDGKM-3.81-3P MALE+FEMALE	1	SET
1	CABLE: PTFE WIRE-24AWG 19/0.12 COPPER TIN PLATED PTFE INSULATION GREY, OD1.15MM	10	PCS

Seconn International Enterprise Co., Ltd.

TOLERANCES		PROJECTION		TITLE			
AS DRAWING				JST Housing to 3.8mm Green color Terminal block male + female/set + black heat shrink tube Cable L:160mm			
DRAWN	Diana	DATE	2019/06/28	PART NO.	SC-S-1906-2801		
SCALE	NONE	SIZE	A4	SHEET	1/1	REV	A