

# DataTale 2.5" Mobile Enclosures

## Touches Your Heart Wherever You Go

- Supports SATA II compliant HDD
- Powers HDD via USB or/and FireWire bus power (upon model)
- Reduces power consumption with HDD spin up/down support
- Connects to host by plug-n-play
- Supports hot-plug and hot-swap
- Combines enclosure and 1394 repeater functionality (AT-S111)
- Enables frequent HDD replacement with copper-pillar reinforced screw guides

The DataTale 2.5" Mobile Enclosure Series offers mobile professionals and power users the pocket-sized compact portable storage solution to carry files, music and photos around. Its glossy case with simple lines presents an elegant extravagance, presenting the external HDD as a neat placement while on usage.

The DataTale **AU-S10** enables access to a SATA HDD via USB 2.0 connection. The **AT-S111** Triple Enclosure offers true connection versatility via USB 2.0, FireWire 400 and 800 ports, which provides fast data transfer speed from appropriately FireWire equipped hosts.

The DataTale 2.5" Mobile Enclosures enable operation of the HDD via USB2.0 or/and FireWire bus power provided by the host. It eliminates the need of AC adapter, while enhancing portability and reducing device footprint.



The copper-pillar reinforced screw guides enhance casing durability to extend product life, regardless of how often the hard drive is swapped.

The hidden LED indicates power and data access statuses. The HDD spin down function ensures efficient operation by reducing power consumption.

With silent operation and the choice of single or triple interfaces, the DataTale 2.5" Mobile Enclosure Series offers the most full-featured and in-style mobile storage solution for your valuable data anywhere on travel.



*Stylish Soft Sleeve  
Protects your HDD on a Go!*



### Specifications

Model	AU-S10	AT-S111
Description	USB 2.0 HDD Enclosure	USB 2.0 / 1394a / 1394b HDD Enclosure
Interface	USB 2.0	USB 2.0 / 1394a / 1394b
Connectors	1 x USB mini-B receptacle	1 x USB mini-B receptacle 1 x 1394a connector 1 x 1394b connector
Data Transfer Rate	USB 2.0: 480Mbit/s	USB 2.0: 480Mbit/s 1394a: 400Mbit/s 1394b: 800Mbit/s
LED	Power On / Access / Power Off	
Dimension	125 x 76 x 16 mm	133 x 76 x 16 mm
Weight (w/o HDD)	85 g	113 g
Power Supply	Bus power from host via mini USB cable	Bus power from host via mini USB cable or 1394a/b bus power

Specifications are subjected to change without notice

### System Requirements

- PC
- 266MHz or faster CPU (800MHz or faster CPU is required for Windows Vista)
  - 64MB of RAM (512MB of RAM is required for Windows Vista)
  - Microsoft Windows 2000, XP, 2003, or Vista
  - One available USB 2.0, 1394a, or 1394b port (upon model)

- MAC
- Macintosh PowerPC or Intel Core Duo processor
  - 64MB of RAM (256MB of RAM is required for Mac OS X 10.4)
  - Mac OS 9.X or higher (PowerPC) / Mac OS X 10.4 (Intel)
  - One available USB 2.0, 1394a, or 1394b port (upon model)

