

Dynamic Bandwidth Management

- On-the-fly upload/download throughput monitoring
- Real-time traffic prioritization (gaming, VoIP, SSH, Telnet, TCP ACK...)
- Profile-based dynamic bandwidth allocation (P2P, gaming, VoIP, web browsing...)
- Intelligent P2P traffic bandwidth allocation
- Optimal bandwidth utilization

Session Management

- Up to 17500 concurrent sessions
- Idle session recycling by LRU (Least Recently Used) session management

MRTG Monitoring

- Real-time MRTG throughput and session monitoring

VNC KVM

- VNC KVM - remote desktop management

Streaming Media Technology

- P2P streaming (Joost, PPStream...)
- RTSP and MMS support (Real, Quick Time, Windows Media Players)
- H.323 video conference support

WAN

- PPPoE, DHCP, Static
- MAC address cloning
- Dynamic DNS (DynDNS, TZO, ZoneEdit)

Wireless

- IEEE 802.11b/g/n(draft 2.0) compliant
- WPA, WPA2, WAP-PSK, WPA2-PSK, WEP 64/128 bits
- WDS (Wireless Distribution System)
- Universal repeater
- Wireless LAN isolation
- 802.1X authentication
- Hidden SSID broadcasting

Network Features

DHCP client/ relay/ server
UPnP
Dynamic DNS
NTP client
DNS cache/ proxy

Firewall

SPI (Stateful Packet Inspection)
Anti-DoS and Anti-spoofing protection
Instant messaging filtering
Layer 2 MAC ACL filtering
Layer 3 IP/protocol ACL filtering
Layer 4 port ACL filtering
Static DHCP and static ARP IP-MAC binding
DMZ and port forwarding (virtual server)

System Management

Web-based management
Configuration backup and restore
Firmware upgrade and downgrade
NTP (Network Time Protocol)
Multiple languages support

Ethernet Port

1 WAN (10/100M) + 4 LAN (10/100M)

Antenna

Detachable dipole antenna x 3

Power Adapter

AC Input: 100V~240V (50~60Hz)
DC Output: 9V

Dimension & Weight

16.8 x 10.5 x 3 cm
250g (excluding antenna)